ADMINSTRATION OF DAMAN AND DIU(U.T.) DIRECTORATE OF MEDICAL & HEALTH SERVICES, PRIMARY HEALTH CENTER, MOTI DAMAN.

No.DHMS/DD/EQUIPMENT-108/2014-15/3623 Dated: 27/12/2014

TENDER NOTICE

Sealed Tender under two bid system are invited on behalf of President of India by the Director of Medical and Health Services, Daman and Diu, Fort Area, Moti Daman from the registered supplier/dealers/manufacturer for the supply of following materials/items for use in 02 Nos. of 108 Ambulances of this Directorate of Medical & Health Services, CHC, Moti Daman with installation / fitting as applicable.

Sr. No.	Description of	Estimated Cost	EMD (in the	Tender Fees
	Materials/Items		form of FDR)	(Non
				refundable)
1.	Instrument / Equipment for 108 Ambulance	`3,30,000/-	`8,250/-	`1,000/-

The tender form along with terms and conditions can be had on payment of Rs.1000/- (non-refundable) from the Directorate of Medical & Health Services, PHC Moti Daman on working day during the office hours upto 20/01/2015 at 11.30 AM. and can also be downloaded from the official website http://daman.nic.in and can submit the same along with tender fee of Rs. 1000/- in form of Demand Draft to be drawn in favour of Director, Medical & Health Services, Daman.

The tender is to be submitted in two bid system which is required to be submitted in separated envelop. The technical Bid should contain all documents, pertaining to technical specification with catalogue including tender form for technical offer, required EMD super scribing on the envelops as "Sealed Cover No.1-Technical Bid. The Financial Bid should only contain schedule of rate and relevant information, super scribing on the envelop as "Sealed Cover No.2-Financial Bid. The tender should reach to this office of the Director, Medical & Health Services, Moti Daman on or before 20/01/2015 upto 12.30 hrs & the Technical Bid will be opened on the same day at 15:30 hrs if possible before the Purchase Committee and in the presence of tenderers/representative of tenderers if any. The mentioned EMD in Col No.4 in form of FDR of Nationalized/Schedule Bank to be drawn in favour of Director, Medical & Health Services, Daman payable at Daman Branch is to be Submitted along with tender.

The suppliers should mentioned the name of the company offer in the technical bid and also to produce sample, if asked and the same is found of inferior quality then financial bid will not be open to the respective agencies.

The Director, Medical & Health Services, Daman & Diu is reserves rights to accept or reject any in part or whole without assigning any reason.

(Dr. K. Y. Sultan)
Director
Medical & Health Services
Daman & Diu

DIRECTORATE OF MEDICAL & HEALTH SERVICES PRIMARY HEALTH CENTRE CAMPUS, MOTI- DAMAN – 396220.

TERMS AND CONDITIONS FOR SUPPLY OF INSTRUMENT / EQUIPMENT FOR 02 NOs. OF 108 AMBULANCES.

<u>Tender Notice No. DHMS/DD/Equipment-108/2014-15/3623</u> Dated: 27/12/2014

Instructions to Bidders:

1.	The rate(s) quoted should be strictly for free delivery at F.O.R. PHC/CHC,
	Moti Daman and will be valid and operative for supply orders issued on or
	before 31/03/2015. All Taxes/ Duties/ Royalties charges payable on sales/transport etc. within
2	and / or outside the UT / State shall be payable by the supplier.
3	Where specification / mark/ manufacture are not specifying by this office, the
3	rates should be quoted only for the first class and standard quality only.
4	The tenderer should specify the name of the manufacturer and complete
•	specification for the items quoted by him along with catalogue of the item to
	be submitted in the Technical bid.
5	The decision of the Tender Inviting Officer acceptance/rejection of any
	articles supplied including the decision for equivalent specifications, standard
	and quality etc. of articles shall be final.
6	(a) The successful tenderer will have to pay within 10 days from the date of
	demand, an amount equal to 10% of the total value of articles, that may
	be order, as the amount of security deposit.
	(b) Non-receipt of Security Deposit within stipulated time limit will result in
	automatic cancellation of the order for supply without any intimation. (c) However in case if any articles are received for which the Security
	Deposit may not have been deposited, the full Security Deposit as may
	be due from the supplier will be recovered from the bills for such articles
7	The amount of Earnest Money paid by the successful Tenderer(s) will be
,	adjusted against the amount of Security Deposit to be paid by the successful
	tenderer(s) as per condition No. 6 above.
8	The tender should be neatly typed or hand written only on list provided by
	this department / letterhead carry the name of supplier and the signature of
	the tenderer with rubber stamp & seal of agency firm. No overwriting,
	correction or erasure will be considered.
9	All bills should be in TRIPLICATE and should invariably mention the number
10	and date of supply order. All bills for amount above Rs.5000/- should be pre-receipted on a Revenue
10	Stamp of Rs.1/ Bills for amount exceeding Rs.5000/- not pre-receipted will
	not be accepted for payment.
11	Each bill in which Sales Tax/Vat is charged must contain the following
	certificate on the body of the bill.
	"CERTIFIED that the goods on which Sales Tax/VAT has been charged
	have not been exempted under the VAT/ Central Sale Tax Act or the Rules
	made there under and the amount charged on account of VAT/Sales Tax on
	these goods is not more than what is payable under the provisions of
10	relevant Act or Rules made there under".
12	The tender will be accepted during working hours up to 20/01/2015 at 12.30 hrs. and opened on same day at 15.30 hrs. if possible in the office of the
	Director, Medical & Health Services, Primary Health Center, Moti Daman in
	the presence of the Purchase Committee and tenderer(s) or their
	representative(s) if present.
13	The Tenders will be opened by the Tender Opening Committee in presence
	of Tenderers or their representatives, if any present in the Office of the
	Tender Inviting Officer.
14	The right to accept or reject without assigning any reasons or all tenders in
	part or whole is reserved with the Tender Inviting Officer and his decision(s)
	on all matters relating to acceptance or rejection of the tenders as a whole or
	in part will be final and binding to all.

15	If the tenderer whose tender is accepted, fails to execute the supply order within stipulated time the Earnest Money Deposit of such tenders will stand forfeited to the Government.
16	In case, the supplier does not execute the supply order placed with him, the
	EMD of the supplier will be forfeited to the Government and the contract for
	the supply shall terminated with no further liabilities on either party to the
	contract.
17	No separate agreement will be required to be signed by the successful
	tender(s) for the purpose of this contract for supply. Rates tendered/offered
	in response to the concerned Tender Notice shall be considered as
	acceptance of all above terms and conditions for supply for all legal purpose.

Con	aditions of contract
1	The rates should be quoted in the prescribed form given by the department. The rates quoted should be inclusive of all taxes, duties, surcharges, cess, freight, loading, unloading, insurance, road permits, packing, (VAT and other taxes if applicable) as applicable. No extra taxes will be given.
2	Orders once placed should be delivered within the given time period and item should be door delivered.
3	No extra charge for packing, forwarding and insurance etc. will be paid on the rates quoted.
4	The rates should be quoted only for the items specifies in the list of requirement and should be for the items of given special mark/manufacture. only would be considered.
5	Rates quoted for items other than the required specification / mark / manufacture will not be considered.
6	The amount of Earnest Money paid by the tenderer(s) whose tenders are not accepted will be refunded to them by cheque or Demand Draft (as may be convenient to the Tender Inviting Officer if the amount is above Rs.200/-) drawn on an branch of State of India or its subsidiary Schedule Bank. Where this mode of payment is not possible the amount will be refunded at the cost of the tenderer.
7	Only on satisfactory completion of the supply order for and on payment of all bills of the supplier, as to be admitted for payment, the amount of Security Deposit/Earnest Money will be refunded after expiry of guarantee/warranty period, if any, or any such date/period as may be mutually agreed upon.
8	The tender inviting officer will consider extension of time for remitting the Security Deposit as demanded. However, in case of denial to consider such extension the supplier is bound to abide by the limit given and liable to make good any loss to the Government on account of his failure to abide by the time limit.
9	 (a) Railway Receipt or other transport document should be drawn in favor of the Officer Inviting Tenders. (b) Railway Receipt or other transport document should not be send by V.P.P. or through any Bank as this being a Government Office it is not possible to clear cash demands of Post Office/Bank for delivery of R.R. or other transport documents unless we have agreed to it as a special arrangements. (c) Railway Receipt or transport receipt should be sent to this Office by Registered Post immediately on dispatch of goods from dispatching end.
10	The supplies of Instrument / Equipment for 02 Nos. of 108 Ambulances of inferior quality standard or of different specifications, content, brand, manufacturer etc. other than that ordered specified and/or incomplete or broken articles will not be accepted. The supplier has to replace the same at his own cost and risk. Intimation of non-acceptance of any stores, Lab items will be sent to the supplier within 10 days from the date of receipt of the stores and the same will be returned to the supplier at his own cost and risk, if he so desires and intimates accordingly within 15 days from the date of dispatch of intimation of the non-acceptance. However, if no communication is received within15 days from the date of communication the tender Inviting Officer will not be responsible for any damage, loss etc. of such rejected articles.

11	In case of failure to replace the accepted and rejected articles from supplies
	made, as mentioned in the conditions, the loss undergone by the
	Government will be recovered from the suppliers Security Deposit/Earnest
	Money or payment due of any bill(s) to the extent required.
12	In case of failure to supply the Instrument / Equipment for 02 Nos. of 108
	Ambulances etc. ordered for, as per conditions and within the stipulated time,
	the same articles will be obtained from the tenderer who offered next higher
	rates or from any other sources, as may be decided by the tender inviting
	Officer and the loss to the Government on account of such purchases(s)
	shall be recovered from the former suppliers Security Deposit/Earnest Money
	or bills payable. The suppliers shall have no any right to dispute with such
	procedure.
12	Extension of time limit for supplies shall be consider by the Tender Inviting
13	Officer. The extension so granted may be with levy of compensation for delay
	in execution of supply order up to 5% of the cost of supplies ordered for at
	the discretion of the authority competent to grant extension of time limit
	provided such request is made well in time, depending upon the
	circumstances and such decision in the matter will be final.
14	Demurrage charges paid by the Tender Inviting Officer on account of delayed
	receipt of dispatch documents intimation will be recovered from the bills
<u></u>	payable to the supplier.
15	If at any time after the order for supply of Machinery/stores/equipment the
	Tender Inviting Officer shall for any reason whatsoever not require the whole
	or part of the quantity thereof as specified in the order the tender Inviting
	Officer shall give notice in writing of the fact to the supplier(s) who shall
	have no claim to any payment of compensation what so ever on account of
	any profit or advantage which the supplier(s) might have derived from the
	supply of articles in full, but which did not derive in consequence of the full
	quantity of articles not having been purchased, nor shall have any claim
	for compensation by reasons of any alterations having been made in the
	original instructions which shall invoice any curtailment of the supply
	originally contemplated.
16	The Earnest Money(s)/Security Deposit(s) paid by the tender(s) earlier
	against any tender(s) or supply order(s) is/are not adjustable with Earnest
	Money or Security Deposit required by these conditions,
17	The tenders/offers received do not confirm with the terms and conditions of
	this office will be summarily rejected. If any firm desires to consider
	exemption from payment of Earnest Money Deposit, certified copies of its
	Registration with D.G.S. & D. should be attached to their tenders.
18	The items as mentioned in the list are the approximate estimates invited and
	actual purchase may more or less. Accordingly the successful tenderer has
	no right for any loss/damages with reference to approximate requirement
	shown in tender and actual requirement.
19	Supplier may ensure the goods at his own cost to safeguard the delivery of
	such goods dispatched by him to the consignee, the department will not be
	responsible for the damage or pilferage of goods during transit.
20	The tenderer should attached copies of certificate of experience in the field of
	supply of lab-item, valid license, proof of fulfilling the norms of
	ISI/ISO/WHO/GMP specification if any, copy of dealership letter, licence for
	import, PAN No., Catalog of the item quoted etc. with his/their tender. It may
	please be noted that the tender received without document reffered above
	shall not be considered.
21	Rates should be quoted in the forms issued from the department and as per
	the requirement asked for.
22	Rates quoted are for PHC/CHC, Moti Daman.
23	Tenderer should enclose along with tender an amount of Rs.3500/- as
43	Earnest Money Deposit in form of DD/ Fixed Deposit Receipt of any
	Nationalized Scheduled Bank payable at Daman in favour of Director,
	Medical & Health Services, Daman. The EMD Submitted other than Form
	mentioned above will not be accepted. Tender received without EMD will be
	summarily rejected.
24	The tender should furnish a declaration regarding Blacklisting/Debarring to
24	participate in the Government tender on the letter head. If the information
	provided found false the tender will be rejected and EMD shall be forfeited.
i	provided round raise the tender will be rejected and LIVID shall be fortelled.

25	The Tenders will be opened by the Purchase Committee in presence of
	Tenderers or their representatives, if any present in the Office of the Tender
	Inviting Officer.
26	This department will specify the expiry date period of Medical Materials etc.
	in the supply order. Generally the expiry date of Medical Materials etc. to be
	supplied by the successful tender must be maximum.
27	Supply quantity of the Medical Materials etc. will be given as per day to
	day requirement and successful supplier shall visit once in a week in order to
	collect the supply order.
28	The tendered quantity is tentative and the actual purchase can be 20% less
	or more than the quantity put to tender for all items and the tenderer is bond
	to supply such requirement without any demur.
29	The tendering firm must be registered with the Sales Tax /VAT department
	and a copy of their registration under the Sales Tax / VAT bearing the TIN
	Number be provided.
30	The terms and conditions dully accepted and signed by the tenderer should
	attached with the Technical Bid.

Signature & Designation of Tender Inviting Officer

(Dr. K. Y. Sultan)
Director
Medical & Health Services
Daman

The above terms and conditions are accepted and are binding to me/us.

Place: Signature of Tenderer & status
Dated: Name of Tenderer with seal of

the firm

NOTE:-Please return one copy of these terms and conditions dully sign with seal of firm along with the tender

ADMINSTRATION OF DAMAN AND DIU(U.T.) DIRECTORATE OF MEDICAL & HEALTH SERVICES, PRIMARY HEALTH CENTER, MOTI DAMAN

ANNEXURE: "B"

TENDER FORM (FINANCIAL BID)

Sr.	Items	Quantity	Suggested Company	Rate per
No.		required	or equivalent	unit/itms.
1	Auto loader – collapsible stretcher	2		
2	Scoop stretcher	2		
3	Spine board with straps and head block	2		
4	Wheel chair	2		
5	Oxygen cylinder – D type	4		
6	Oxygen cylinder P0rtable – 1.8 ltr	2		
7	Suction pump	2		
8	Oxygen key	2		
9	Oxygen regulator	2		
10	Humidifier bottle	2		
11	Flow meter	2		
12	Ambu Bag Adult	2		
13	Ambu Bag Child	2		
14	Torch	2		
15	Needle & syring destroyer	2		
16	Thermometer – Digital	2		
17	Kidney Tray - 20 c.m. S.S.	2		
18	Urine pot – Plastic	2		
19	Bed Pan – Plastic	2		
20	Sputum Cup - S.S.	2		
	Grand Total – " A"			

The Rates quoted should be inclusive of all taxes, forwarding & packing, FOR delivery, successful installation & fitting as applicable. L1 shall be arrived on the Grand Total-" A" for supplying, installation & fitting of products.

Place:	Signature and Seal of Tenderer
Dated:	

ADMINSTRATION OF DAMAN AND DIU(U.T.) DIRECTORATE OF MEDICAL & HEALTH SERVICES, PRIMARY HEALTH CENTER, MOTI DAMAN

ANNEXURE: "A"

TENDER FORM (TECHNICAL BID)

Sr.	Item	Quantity	Company offered
No.		required	
1	 Auto loader – collapsible stretcher Automatic Loading, made of aluminum alloy. Collapsible. Wheeled to slide into the ambulance with ease with out damaging the ambulance floor. One person should be able to raise and lower it into an ambulance easily. Provision for head end elevation adjustable. Sitting posture for breathless patients - Maximum Angle of the Back 60° Side Railings to prevent fall of patients either side and to hold medical equipment IV fluid holding rod to go with the Stretcher Should be light, safe and reliable trouble free. Levers to control front and hind legs to fold while loading the stretcher in to the ambulance. Lock to lock & unlock the legs to prevent collapse of the stretcher while standing Locks for the wheels. Straps 3 in number to restrain the patient. Fixing devices to secure the stretcher in place not allowing side to side or vertical movements in the ambulance while on run. 50 mm thick high density foam mattress with Head rest -up holstered with water proof and fire proof rexin Net weight: 40 Kgs Gross Weight 50kgs Bearing Pressure or minimum load: 159Kgs. Product dimensions: 190*54*90 cms 	2	
3	 Scoop stretcher Should be light, safe and reliable. Made of aluminum alloy Clutch Design (Lateralised / in center) so that the stretcher can be divided into left and right halves. Adjustable length according to patient's height. Easy to lock and unlock 3 Quick release buckle belts Dimensions: Max. Size (L*W*H): 225*45*6cm & Min. Size (L*W*H) 168*43*7cm Net weight: 9Kgs Stretcher bearing: 159kg 190*54*90cm Spine board with straps and head block High Density Poly ethylene - Single piece Rigid, Light & Floatable Resistant to bumps and corrosion Non absorbent, immune to infiltrations Easy to clean- water & soap should be enough. X ray & MRI compatible Net weight: 9Kgs Load Capacity: 159 Kgs L*W*H: 184 * 45 * 5 Rigid Head Blocks 	2	

	where the state of	_	
4	Wheel chair	2	
	Should be light, safe and reliable. Made of		
	aluminum alloy		
	With 4 wheels		
	• Folded size : 93*51*16		
	Back Height: 91 cms Width: 50cms		
	Seat height : 49 cms Width : 50 cms		
	Net weight : 8 Kgs		
	Pull through, telescoping long handles built in		
	to lift patients & carry them through narrow		
	passages.		
	Two handles on the top to facilitate the lifting		
	of patients , working in harmony with		
	telescoping handles		
	Loading Weight : 159 kgs		
5	Oxygen cylinder – D type	4	
	Chrome Molybdenum Alloy 34 Cr		
	Capacity :: 46.7 Ltr cap		
	Working pressure : 150kg/cm2 at 15 c		
	Test Pressure: 250kg/cm2 at 150 c		
	Wall thickness: 5.5 mm min		
	• Gas (O2): 7 cumtr (7000 ltr of O2)		
	Standard : IS 7825 part II		
	• Valve : IS 3224		
	Statutory certifications : ISI Standards,BMP		
	Certification WHO & Certified by Dept		
	Explosives –Gol		
6	Oxygen cylinder Portable – 1.8 ltr	2	
	Max. Working Pressure at 150 C : 150kgf/cm2	_	
	Test Pressure : 250 kgf/cm2		
	Water capacity : 1.8 ltrs		
	Gas Capacity (Cu.m.) : 0.15 Cu.m.		
	Min. Wall Thickness 't" (mm) : 3.2mm		
	• Length 'L' Approx. (mm) : 310mm		
	Tare weight approx. (kg) : 2.5 Kg. Built in / attached with Pressure gauge regulator.		
	Built in / attached with Pressure gauge, regulator Oxygen Transfer system from Bulk D-type cylinder to		
	Portable cylinder		
7	Suction pump	2	
	0 to 30 Lits flow rate	_	
	High Vacuum below - 300 mm of Hg & High Vacuum of 1900 mm of Hg		
	Vacuum of - 800 mm of Hg		
	Portable & with a mounting bracket.		
	Battery back up of 90 minutes minimum-		
	rechargeable in ambulance		
	Collection bottle 600 ml capacity and e-		
	Sterilizable		
	0.00		i
	Overflow protection ensured		
	Overflow protection ensured		
8	Overflow protection ensuredWeight not more than 5 Kgs	2	
8	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key	2	
8	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release 	2	
8	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release 	2	
	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder.		
8	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator	2	
	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of		
	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety		
	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve.		
	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder 		
	Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in bull nose nipple. 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in bull nose nipple. The body of the regulator made of brass 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in bull nose nipple. The body of the regulator made of brass forging. 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in bull nose nipple. The body of the regulator made of brass forging. Stainless Steel opposing springs (not mild 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in bull nose nipple. The body of the regulator made of brass forging. Stainless Steel opposing springs (not mild steel) to with stand opposing pressure. 		
	 Overflow protection ensured Weight not more than 5 Kgs Oxygen key Matching Key cum Spanner to release oxygen - same key may be used to release oxygen from portable cylinder. Oxygen regulator 2 stage pressure reducer outlet pressure of approx.4.2 Kg / Sq.cm (60 lbs / sq.in) safety valve. Automatically maintain a constant flow rate irrespective of changing volume of cylinder contents. Should the oxygen line distal to the regulator blocked, the regulator automatically has to prevent the build up of an excessive pressure in the apparatus and tubing between the outlet of the regulator and the obstruction. Pressure gauge to indicate the contents Bull Nose Hex nut & nipple made of Brass Rod instead of casting and a filter placed in bull nose nipple. The body of the regulator made of brass forging. Stainless Steel opposing springs (not mild 		

10	 Made from Neoprene rubber/ steel O.D - 53.00 mm Thickness - 2.0 mm minimum Valve Seat for O2 are of O.D 10 mm Thickness of 2.5 mm Safety Relief Valve with large hole to prevent any accumulation of pressure inside the cover (when more than 8 kg the pressure should automatically get released from safety relief valve- due to accidental leakage of gas from inside of the regulator. Humidifier bottle Unbreakable jar with metal screw on cap fitted on top inlet and side outlet tubes (metal/ABS). The inlet tube ends in a specially designed diffuser from which oxygen is bubbled through water before reaching the outlet. Humidifier - screw on type - Metal Inlet & outlet provided with 1/2" BSF threads that can be screwed on directly to the outlet of the flow meter. 	2	
11	 Flow meter Rotary pin valve control to permit adjustment of the flow rate to any desired level between 0 – 15 ltrs /min. Jacketed type shatter proof tubes on units Body made of Brass Outlet at bottom of the unit to have a removable nipple (metal). Transparent flow tube made of poly carbonate for durability & un-breakability. Flow Tube - Calibrated to indicate flow from 0 to 15 ltr/min Bobbin to be made of stainless steel to avoid rusting and unaffected by oxygen. Back pressure compensated Multiple Oxygen Delivery System 	2	
12	 Ambu Bag Adult 1600ml. self inflating double ended silicone bag with mounts Siliconised Side feed oxygen inlet Type "L" non-rebreathing valve Size 4 Clearhood facemask with silicone cuff 1.5mtrs oxygen enrichment tubing In carrying case. 	2	
13	 Ambu Bag Child 500ml Self inflating double ended silicone bag with mounts Side feed oxygen inlet Type "L" non-rebreathing valve with pressure limiting device 40cms of water Size 0A Circular Paedi All Silicone facemask Reservoir Hose (5037) with Adaptor (9034) to provide higher oxygen & 1.5mtrs oxygen enrichment tubing Carrying case. 	2	
14	 Torch For quick and effective evaluation of pupillary reflex. Spot illumination with out peripheral ring of light. Easy to handle and easy to power on and off. 	2	
15	 Needle & Syringe Destroyer Burn the needle electrically and cut the syringe tip. Maximum weight 2.5 Kgs Motion Tolerant 	2	

16	 Thermometer – Digital Battery operated, with on and off audio alarm, Measurable in Fahrenheit and Centigrade. Memory of the last reading 	2	
17	 Kidney Tray - 20 c.m. S.S. 20 cms. x 15 Cm x 4 cm 18/ 8 Stainless Steel. 500 ml capacity 	2	
18	Urine pot – Plastic Male: Clear plastic translucent finish; Stain resistant plastic, Graduated 1000 ml capacity Male; Autoclavable Female: Clear plastic translucent finish; Stain resistant plastic, Graduated 1000 ml capacity Female; Autoclavable	2	
19	Bed Pan – Plastic Resistant to stains & cracks Contoured design molded plastic for adults with wide seat Can be boiled or autoclaved up to 275 degrees F 350-pound weight capacity 'pontoons' on sides to aid stability Recessed tailbone area for comfort	2	
20	 Sputum Cup - S.S. Cup with hinged cover to close completely made of high finish 18/8 steel 	2	

oeai

Signature and Seal of Tenderer

Date