

**U.T. Administration of Daman and Diu,  
O/O Medical Superintendent,  
Government Hospital, Daman**

No.GHD/E-TENDER/HD/2014-15/2667


Dated: 19 .01.2015

**E- TENDER NOTICE**

The Medical Superintendent, Government Hospital, Daman on behalf president of India, invites tenders for following items through on-line on [http: Daman.nprocure.com](http://Daman.nprocure.com) form the manufacturer/Authorized Dealers/Suppliers having valid Licence.The tender notice also available on [www.nic.daman.in](http://www.nic.daman.in).

Sr.No.	Description	Total estimated Cost	EMD (in the form of FDR)	Tender fees (non refundable)
01	Purchase of Hospital Equipment and Furniture	Rs.9,50,000/-	Rs.28,500/-	Rs.2,000/-

**The tender notice sets with terms and condition are available on the website [www.nic daman.in](http://www.nic.daman.in) and [www.nprocure .com](http://www.nprocure.com) last date for uploading the tender is up to 12.hrs on 09/02/2015**

  
**Medical Superintendent,  
Government Hospital,Daman**

**U.T.ADMINISTRATION OF DAMAN & DIU  
O/O THE MEDICAL SUPERINDENDENT,  
GOVERNMENT HOSPITAL, DAMAN  
DAMAN**

**TERMS & CONDITIONS FOR THE SUPPLY HOSPITAL EQUIPMENT AND  
FURNITURE FOR GOVERNMENT HOSPITAL, DAMAN**

E-Tender Notice No. No.GHD/E-TENDER/2014-15/2667 Dated 19 /01/2015

1. The rate(s) quoted should be strictly for free delivery at F.O.R. Government Hospital, Daman and will be valid and operative for supply orders issued on or before 31-03-2015
2. The rates should be quoted inclusive of all taxes, installation & commissioning charge etc.
3. Except C.S.T. all other Taxes/Duties/Royalties Charges payable on the sales/transport etc. within and/or outside the state of supplier shall be payable by the supplier.
4. No extra charge for packing, forwarding and insurance etc. will be paid on the rates quoted.
5. The rates should be quoted only for the items specified in the list of requirement and should be for the items of given special mark/manufacture.
6. Rates quoted for items other than the required specification/mark/manufacture may not be considered. However, indigenous manufactures may quote their own makes provided the specifications confirm to the standard(s)/requirements of the given Specifications /mark/ manufacturer.
7. Where specifications/mark/manufacture are not specifying by this office, the rates should be quoted only for the 1st class and standard quality. The specification asked for should be written clearly as "Yes' or 'No'"
- 8.. The Tenderer should specify the name of the manufacturer for the items quoted by him along with catalogue of the item.
- 9.. The decision of the Tender Inviting Officer for acceptance/rejection of any articles supplied including the decision for equivalent specifications, standard and quality etc. of articles shall be final.
- 10 **The Tenderer should send in advance or enclose along with technical bid an amount of Rs. 28,500/- (Rupees Twenty Eight Thousand five hundred only ) as Earnest Money Inform of Demand Draft / F.D.R. of any scheduled Bank payable at Moti Daman in favor of the officer inviting tenders i.e. Medical Superintendent, Daman. The E.M.D. submitted other than form mentioned above will not be accepted. Tender received without Earnest Money Deposit will be summarily rejected.**
11. (a) The successful Tenderer will have to pay within 10 days from the date of demand an amount equal to 10% of the total value of articles, that may be order, as the amount of security deposit.  
(b) Non-receipt of Security Deposit within stipulated time limit will result in automatic cancellation of the order for supply without any intimation.  
(c) However in case if any articles are received for which the Security Deposit may not have been deposited, the full Security Deposit as may be due from the supplier will be recovered from the bill(s) for such articles.

The amount of Earnest Money paid by the successful Tenderer(s) will be adjusted against the amount of Security Deposit to be paid by the successful Tenderer(s) as per condition No. 12 above.

- 13 The tender should be neatly typed only on letterhead carry the name of supplier and the signature of the Tenderer. No overwriting, correction or erasures will be considered.
- 14 The amount of Earnest Money paid by the Tenderer(s) whose tenders are not accepted will be refunded to them by Cheque or Demand Draft (as may be convenient to the Tender Inviting Officer if the amount is above Rs.1000/- drawn on an branch of State of India or its subsidiary Schedule Bank. Where this mode of payment is not possible the amount will be refunded at the cost of the Tenderer.
15. Only on satisfactory completion of the supplies ordered for and on payment of all bills of the supplier, as to be admitted for payment, the amount of Security Deposit/Earnest. Money will be refunded after expiry of guarantee/warranty period, if any, or any such date/period as may be mutually agreed upon.
16. The tender inviting officer will consider extension of time for remitting the Security Deposit as demanded. However, in case of denial to consider such extension the supplier is bound to abide by the limit given and liable to make good any loss to the Government on account of his failure to abide by the time limit.
17. (a) Railway Receipt or other transport document should be drawn in favor of the Officer Inviting Tenders.  
(b) Railway Receipt or other transport document should not be send by V.P.P. or through any Bank as this being a Government Office it is not possible to clear cash demands of Post Office/Bank for delivery of R.R. or other transport documents unless we have agreed to it as a special arrangement. (c) Railway Receipt or transport should be sent to this Office by Registered Post immediately on dispatch of goods from dispatching end.
18. The supplies of Store equipment etc. of inferior quality standard or of different specifications, brand, manufacturer etc. other than that ordered specified and/or incomplete or broken articles will not be accepted. The supplier will have to replace the same at his own cost and risk. Intimation of non-acceptance of any stores Machinery and equipment etc. will be sent to the supplier within 10 days from the date of receipt of the stores and the same will be returned to the supplier at his own cost and risk, if he so desires and intimates accordingly within 15 days from the date of dispatch of intimation of the non-acceptance. However, if no communication is received within 15 days from the date of communication the tender Inviting Officer will not be responsible for any damage, loss etc. of such rejected articles.
19. In case of failure to replace the accepted and rejected articles from supplies made, as mentioned in the conditions, the loss undergone by the Government will be recovered from the suppliers Security Deposit/Earnest Money or payment due of any bill(s) to the extent required.
- 20 In case of failure to supply the store, machinery and equipment etc. ordered for, as per conditions and within the stipulated time, the same articles will be obtained from the Tenderer who offered next higher rates or from any other sources, as may be decided by the tender inviting Officer and the loss to the Government on account of such purchases(s) shall be recovered from the former suppliers Security Deposit/Earnest Money or bills payable. The suppliers shall have no any right to dispute with such procedure. (1)

Extensions of time limit for supplies shall be consider by the Tender Inviting Officer. The extension so granted may be with levy of compensation for delay in execution of supply order up to 5% of the cost of supplies ordered for at the discretion of the authority competent to grant extension of time limit provided such request is made well in time, depending upon the circumstances and such decision in the matter will be final.

22. Demurrage charges paid by the Tender Inviting Officer on account of delayed receipt of dispatch documents intimation will be recovered from the bills payable to the supplier.
23. (i) The supplier(s) of the machinery and equipments shall have to supply spare parts as and when required in on an agreed basis i.e. on agreed on the published catalogue/price lists for an agreed period.  
(ii) The supplier (s) shall give adequate advance notice before any spare parts goes out of production to enable the tender Inviting Officer to order for spare parts required in one lot for the life time of respective machinery. (iii) If mutually agreed to the supplier(s) shall make available the blue prints of drawing etc. of the spares if any when required in connection with main machinery/equipments.
24. If at any time after the order for supply of Machinery/stores/equipment the Tender Inviting Officer shall for any reason whatsoever not require the whole or part of the quantity thereof as specified in the order the tender Inviting Officer shall give notice in writing of the fact to the supplier(s) who shall have no claim to any payment of compensation what so ever on account of any profit or advantage which the supplier(s) might have derived from the supply of articles in full, but which did not derive in consequence of the full quantity of articles not having been purchased, nor shall have any claim for compensation by reasons of any alterations having been made in the original instructions which shall invoice any curtailment of the supply originally contemplated.
25. The Earnest Money(s)/Security Deposit(s) paid by the tender(s) earlier against any tender(s) or supply order(s) is/are not adjustable with Earnest Money or Security Deposit required by these conditions,
26. All bills should be in DUPLICATE and should invariably mention the number and date of supply order.
27. All bills for amount above Rs.5000/- should be pre-receipted on a Revenue Stamp of proper value. Bills for amount exceeding Rs.5000/- not pre-receipted on Revenue Stamp of proper value will not be accepted for payment.
28. Each bill in which Sales Tax is charged must contain the following certificate on the body of the bill. **"CERTIFIED that the goods on which Sales Tax has been charged have not been exempted under the Central Sale Tax Act or the Rules made there under and the amount charged on account of Sales Tax on these goods is not more than what is payable under the provisions of relevant Act or Rules made there under"**.
29. The Purchase Committee will open the Tenders in presence of tenderers or their representatives, if any present in the Office of the Tender Inviting Officer. The Purchase Committee will first open the technical bid and considering the technical specification of Surgical Instrument. The Committee will open the financial bid only of those firms who are qualified for technical bid as per minimum specifications given by the department.

The right to accept or reject without assigning any reasons any or all tenders in part or whole is reserved with the Tender Inviting Officer and his decision(s) on all matters relating to acceptance or rejection of the tenders as a whole or in part will be final and binding to all.


31. The tenders/offers received do not conform to the terms and conditions of this office will be summarily rejected. If any firm desires to consider exemption from payment of Earnest Money Deposit, certified copies of its Registration with D.G.S. & D. should be attached to their tenders.
32. If the tenderers whose tender is accepted, fails to execute the supply order within stipulated time the Earnest Money Deposit of such tenders will stand forfeited to the Government.
33. In case, the supplier does not execute the supply order placed with him, the EMD of the supplier will be forfeited to the Government and the contract for the supply shall terminated with no further liabilities on either party to the contract.
34. No separate agreement will be required to be signed by the successful tender(s) for the purpose of this contract for supply. Rates tendered/offered in response to the concerned Tender Notice shall be considered as acceptance of all above terms and conditions for supply for all legal purpose.
35. The items as mentioned in the list are the approximate estimates invited and actual purchase may more. Accordingly the successful Tenderer has no right for any loss/damages with reference to approximate requirement shown in tender and actual requirement.
36. **The last date of downloading of on line tender documents is up to 09.02.2015 By 12.00 Noon. The last date of submission of online tender document is up to 09.02.2015 By 13.00 hours on line opening of price bid if possible is on to 09.02.2015 at 15.00 hours. The Bidder have to submit price bid in Electronic format only, till the Last date and time for submission. Price bid is physical format shall not be accepted in any case.**
37. Supplier may ensure the goods at his own cost to safeguard the delivery of such goods dispatched by him to the consignee; the department will not be responsible for the damage or pilferage of goods during transit.
38. The tenderers should attached details of civil work to be carried out by this Department for installation/commissioning of Incinerators.
39. The tenderer should attached copies of certificate of experience in the field of supply of Hospital Equipment and Furniture, valid license, proof of fulfilling the norms of IS or ISO, CE Certified specification if any, copy of dealership letter, license for import, PAN No., Catalog of the item quoted etc. with his/their tender. It may please be noted that the tender received without document referred above shall not be considered.
40. The tenderer may be called for a Sample / demonstration of the items quoted for which he/she/they will be informed one week in advance for arranging the necessary Sample / demonstration in the hospital on a suitable date & time failing which the tender will be rejected.
41. **AMC: The rate of AMC should be for the period of three years from the expiry of Guarantee/Warranty period of one year and should written separately in the financial bid year-wise. The decision to accept the tender with or without AMC is reserve with the purchase Committee.**

2. The Bidder should not have quoted price lower than quoted in this tender to any Govt./semi Govt./public sector undertaking, Bidder should enclose affidavit to that effect on a Noon Judicial stamp paper of Rs.10/-

43. The terms and conditions dully accepted and signed by the tenderer should attached with the technical bid.

44. The Financial bid has to filled in prescribed format online. [www.nprocure.com](http://www.nprocure.com).

Signature & Designation of  
Tender Inviting Officer

  
(DR.SUNIL P.AMONKAR)  
Medical Superintendent  
Government Hospital, Daman

**The above terms and conditions are accepted and are binding to me/us.**

**Place:**  
**Dated:**

**Signature of tenderers**  
**Name of tenderers with seal of the firm**

U.T.ADMINISTRATION OF DAMAN & DIU  
O/O THE MEDICAL SUPERINDENDENT,  
GOVERNMENT HOSPITAL, DAMAN  
DAMAN

Tender Notice No.GHD/E-TENDER/2014-15/

Dated 19 /01/2015

**SPECIFICATION FOR SURGICAL EQUIPMENT AND HOSPITAL FURNITURE**

Sr.No	Description	Unit
01	<p><b>I.C.U. BED SHOULD ON FULLY MOTORISED WITH A PRESS OF A BUTTON CARDIAC CHAIR POSITION</b></p> <p>Overall Size: Approx 2160mm L x 1020 mm W x 450mm To 810 mm H (Without Mattress).            Bed Platform frame size 2070mmL x 960mm W            Mattress Platform size 1900mm L x 865mm W  <b>Five section Poly Propylene detachable top fitted on four section top bed frame with transverse and raised cup designs to prevent mattress slippage and for easy breathing of mattress.</b>            Backrest and leg rest both shall have detachable mattress guards. (3nos on each section respectively.)            Back rest - min 45% of the frame length.            Backrest, knee rest and height adjustment positions operated by Electro mechanical adjustment through hand set; an additional nurses' control hand set, in addition for operating and locking of above functions and shall have trendelenburg/reverse trendelenburg positions .            Simultaneous electromechanical adjustment of backrest and knee rest on both, hand set and the additional nurses' hand set.            Lower leg section can be adjusted by Ratchet Mechanism.            One touch key for converting bed into a high cardiac chair position of upto 17° on both hand set and the additional nurses' hand set.            One touch key for flattening of the bed at the lowest height for 'CPR' on the nurses' hand set            One touch key for 'Emergency trendelenburg position' on the nurses' hand set.            Battery backup with inbuilt battery charger shall be provided.            The hand set and the nurse hand set shall have indications for power on and the battery charge.            Manual pull lever on both sides of bed to quickly bring backrest to a flat position            Degree indicator required on both the side for backrest, kneerest &amp; Trendelenburg / Reverse trendelenburg positions and I V Rod provision is to be on both the angle indicators.            All electro mechanical actuators needs to be compatible with class of IP 54.            Backrest and kneerest shall retract as they are individually and simultaneously raised.            Bed frame shall be mainly made from 50x25mm x 2 mm thick ERW tube with proper support. This frame shall be fitted on the base frame mainly made of 60 x 30 x 1.6mm ERW tubes on various supporting links.            The base frame shall be mounted on 125mm dia non-rusting twin wheel castor with central and directional locking mechanism.            Twin wheel castors with castor housing and wheels made from high grade non floor-staining synthetic materials with integrated thread guards. Wheel centre having precision ball bearing to run smoothly.            The bed shall have polymer moulded head &amp; foot side panels detachable by hand without need of any tool. Four corner rubber buffers.            Bed shall have split type swing down railings, 2 nos on each side (Head &amp; middle section) made from polymer moulded material. These shall be fitted to the mattress support sections and should be able to raise and lock through spring lock mechanism through an operating lever. When put down, they should undergo and level with the bed frame.            Railings shall avoid any finger and neck entrapments and comply with IEC standard 60601-2-52            There shall be four locations on the bed to hold one stainless steel Saline rod 12mm dia with 31.7mm dia, 18 g stainless steel outer covering tube with a knob to mount syringe pump.            Built in bed extension of min 200 mm shall be provided.            The bed shall have pullout linen-holder made of S.S rod.            Bed should have the provision of night lamp facility.            Finishing &amp; workmanship in the medical furniture is of prime importance and must be of high standard. All corners shall be rounded off so that there shall be no sharp corners and holes, should be burr free.            All Process Parameters to be as per documented IMS Procedures for Quality Assurance (ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 &amp; ISO 13485:2003 Quality Management Systems).            M.S. tubular parts, linkages, flats are to be In-house, pretreated, shot blasted and Epoxy powder coated as per ISI standards, 50 to 60 microns.</p>	

**Accessories:**

- 1 12mm diameter Stainless Steel SS304 Telescopic Heavy Duty I.V. Rod to hold syringe pumps and IV fluid bottles with 2 hooks - 1no. (Stainless Steel) with provision to park when not in use.
- 2 Urine Bag Holder - 1no.
- 3 Chart Holder - 1 No.
- 4 Four Section Mattress with 4" thick PU Foam of 40 Density covered with PVC Rexine - 1no. Including mattress for bed extension.
- 5 Oxygen cage cylinder cage.
- 6 Traction pulley attachment for trauma cases.
- 7 X-Ray permeable backrest with cassette holder in lieu of backrest with PP top.
- 8 3<sup>rd</sup> railing on both the side at leg end.

2

**Crash Cart**

Overall Approx Dimension :

Pushing Handle to Oxygen Cylinder Cage Provision : 1040mm x 595mm

Platform Dimension : (Top Polymer Moulded Panel) : 560mm x 370mm

Max. Height : 1625mm

Top Should have Polymer moulded Panel.

All the drugs, life saving equipments and disposable ampoule should be secured with sealing and locking mechanism to lock the entire cart.

Should be easy to clean.

Should have in-built trash can for temporarily storing the cut out disposable ampoules.

Should have swing type switch board with 2 socket and 1 switch with cable on the real side.

Should have cardiac massage board, Dimension 710 x 390mm with 6mm thick

Should have 4 different size drawers with common locking mechanism

-Upper Drawer with ABS Tray - Dimension - 560x340x65mm

-Middle Drawer with ABS Tray- 2 nos - Dimension - 560x340x145mm

-Lower Drawer with ABS Tray - Dimension - 560x360mm

Should have Polycarbonate partition plate for Drawer and second drawer.

Should have chart/file holder

Should have Cather Holder - 2nos

Should have Oxygen Cylinder cage

Should have SS I.V.Rod with Two hooks.

Should have De-fib tray holder platform of 300 x 200mm

Should have two S.S. detachable top shelves, one without lid and one with five polycarbonate partitions and cover lid at eye level.

Should have polycarbonate partition plates and scissor holder

Twin wheel castor 125mm dia. Two with break and two without break.

All MS parts are passed through 8 tanks Pretreated & powder coated process. All SS parts finished with Matt Polish.

All Process Parameters to be as per documented IMS Procedures for Quality Assurance ( ISO 9001:2008

Overall Approx Dimension :

Pushing Handle to Oxygen Cylinder Cage Provision : 1040mm x 595mm

Platform Dimension : (Top Polymer Moulded Panel) : 560mm x 370mm

Max. Height : 1625mm

Top Should have Polymer moulded Panel.

All the drugs, life saving equipments and disposable ampoule should be secured with sealing and locking mechanism to lock the entire cart.

Should be easy to clean.

Should have in-built trash can for temporarily storing the cut out disposable ampoules.

Should have swing type switch board with 2 socket and 1 switch with cable on the real side.

Should have cardiac massage board, Dimension 710 x 390mm with 6mm thick

Should have 4 different size drawers with common locking mechanism

-Upper Drawer with ABS Tray - Dimension - 560x340x65mm

-Middle Drawer with ABS Tray- 2 nos - Dimension - 560x340x145mm

-Lower Drawer with ABS Tray - Dimension - 560x360mm

Should have Polycarbonate partition plate for Drawer and second drawer.

Should have chart/file holder

Should have Cather Holder - 2nos

Should have Oxygen Cylinder cage

Should have SS I.V.Rod with Two hooks.

Should have De-fib tray holder platform of 300 x 200mm

Should have two S.S. detachable top shelves, one without lid and one with five polycarbonate partitions and cover lid at eye level.

Should have polycarbonate partition plates and scissor holder

Twin wheel castor 125mm dia. Two with break and two without break.

All MS parts are passed through 8 tanks Pretreated & powder coated process. All SS parts finished with Matt Polish.

All Process Parameters to be as per documented IMS Procedures for Quality Assurance ( ISO 9001:2008



### Multi Treatment Chair

Multi Treatment chair can be used for Dialysis, Blood Transfusion, Oncology and Chemotherapy

Overall size: 1860mm D x 940mm W x 595mm to 730mm H

Seat Width :610mm

Fully Motorised: Backrest , Height , Lower Leg and Chair Position operated on Motors

Trendelenburg Tilt of 15 degrees

One Push button for Chair Position, Flat Position for CPR,

Combined Electrical Backrest and Lower Leg to attain Chair Position

Should have Pair of Removable, Adjustable Armrests with Back and Forth, Sideways and Up-Down Movements. Overall Approx Dimension 525mm L X 155mm W. with 60mm upholstery

Base Frame should be made of Curvy 60mm X 30 mm X 16 G which is welded to round tube of 80mm Dia X 16 G

The Three Section tops should be made of 10 G thick of CRCA for backrest , Seat and Upper Leg and should be supported by 75mm thick upholstery

#### Electrical Specifications:

Nominal 230 V Ac

**Switch Mode Power Supply:** Operating Range from 90 V to 300 V 47/63 Hz, Max 2.A

Electrical Shock Protection : Class I

Degree of Shock Protection : Type B

Liquid Ingress Protection : IP54

Rechargeable Batteries : 2 X 12 Volt Sealed Lead / Acid Gel

Duty Cycle : 10% (Two minutes for Every Eighteen minutes)

All MS parts are passed through 8 tank Pre-treatment and should be Epoxy powder coated.

Finishing & workmanship in the medical furniture is of prime importance and must be of high standard. All corners shall be rounded off so that there shall be no sharp corners.

All Process Parameters to be as per documented IMS Procedures for Quality Assurance (ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 & ISO 13485:2003).

#### Optional Accessories

1	Food Table / Reading Table
2	I.V. Pole

4.

### EMERGENCY AND RECOVERY TROLLEY

Overall Size: 1905mm L x 710mm W x 660mm To 910 mm H.

Stretcher dimension approx: 1830 mm L x 555 mm W.

Two section top. Height adjusted by foot operated maintenance free hydraulic pump.

Height adjustment shall be obtained by hydraulically operated mono block type linear actuator pump foot operated actuation having stroke of 140+/- 5mm, push force 10KN at 270 bar, number of complete pumpstroke 22 to 24 for full stroke length.

X-ray permeable removable stretcher, in two section

Backrest raised on ratchet.

Quick trendelenburg as well as reverse trendelenburg positions shall be provided with easily accessible operating handle provided with two gas springs for easy action

S.S. saline rod with 12mm dia S.S. rod shall telescope in SS socket tube approx 15.8 mm dia x 18G welded on angular base bracket of 14G SS sheet. Nylon bracket provided to prevent colour damage It could be placed at four different locations.

Complete with sliding X-ray cassette holder, storage tray. Trolley shall be mounted on 125mm dia non-rusting castor wheels two with brakes and two without.

Castor made from high grade non floor-staining synthetic materials with integrated thread guards. Wheel centre having precision ball bearing to run smoothly.

Complete with corner buffers, one on each corner synthetic rubber covered handles

Oxygen cylinder cage

It shall have a pair of Stainless steel tuck down type railings made of 19mm dia x 18G tube fitted with M.S. brackets.

Effective railing height above main frame is approx. 235 mm & length of the railing is 1175 mm

Finishing & workmanship of the medical furniture is of prime importance and must be of high standard. All corners shall be rounded off so that there shall be no sharp corners

M.S. tubular parts, linkages, flats are to be In-house, pretreated, shot blasted and Epoxy powder coated as per ISI standards, 50 to 60 microns.

All Process Parameters to be as per documented IMS Procedures for Quality Assurance (ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 & ISO 13485:2003 Quality Management Systems).

#### Accessories:

- 1 Rexine covered 25mm thick rubber mattress.

5.

### Rigid (Fixed Wheel Chair)

Overall size: 1120mm D x 670mm W x 920mm H approx..

Tubular frame work of 22mm OD x 18 G tube except for the four widthwise stays of 19.05mm OD c 18 G tubes. Fully Stainless Steel

For self propulsion, Two hoops of 15.8mm OD x 18 G S. S. tube mounted on rims of solid rubber typed wheels 457mm (18") seat and back are made of 18 G M.S. sheets.

Two foldable cast aluminum foot rest and two 200mm dia strong swiveling castor wheels provided in the front.

All S S part 304 Grade and Matt finished

Finishing & workmanship in the medical furniture is of prime importance and must be of high standard. All corners shall be rounded off so that there shall be no sharp corners

### **Birthing Bed (Motorised)**

Over all Size: 2155mm L when extended x 1010 mm W x 520 mm To 880 mm H (Without Mattress).

Three section high pressure laminated top. It shall have detachable laminated top for middle section and leg section for ease of cleaning.

Leg section can be telescoped under backrest for lithotomy position.

Backrest, trendelenburg & reverse trendelenburg and height adjustment position operated by Electro mechanical adjustment thru hand set; battery backup with inbuilt battery charger shall be provided. The hand set shall have indications for power on and the battery charge.

All electro mechanical actuators need to be compatible with class of IP 54.

The bed shall have work simultaneously on two actuators system for raising and lowering height.

Bed frame made mainly from 60 x30mm x 1.6mm mm thick ERW tube with proper support. This frame shall be fitted on the base frame mainly made of 60 x 30 x 1.6mm ERW tubes on various supporting links.

The base frame shall be mounted on 125mm dia non-rusting castor wheels with central and directional locking mechanism and pedal operated at the head end of the bed. Castor made from high grade non floor-staining synthetic materials with integrated thread guards. Wheel centre having precision ball bearing to run smoothly.

The bed shall have easily detachable moulded head & foot side panels. Four corner rubber buffers.

Bed shall have swing down type railings; Railing shall be made from non-rusting moulded material. These shall be fitted to the mattress support sections and should be able to raise and lock through spring lock mechanism through an operating lever.

S.S. saline rod with 12mm dia S.S. rod shall telescope in SS socket tube approx 15.8 mm dia x 18G welded on angular base bracket of 14G SS sheet. Nylon bracket provided to prevent colour damage It could be placed at two different locations.

Patient's bearing down handgrips should be made of 22mm dia 18 G stainless steel tube fixed with PVC handle and should have location adjustability for patient's convenience.

A pair of upholstery aluminum lithotomic crutches mounted on S.S. rods.

Waste collecting removable stainless steel tray shall be provided at perennial recess.

It shall have foot support for high / low chair position.

The backrest and middle section shall have 75 mm thickness foam mattress P.U. 40 D. with rexine cover and zip. The leg section shall have 130mm thickness for propose alignment with other adjacent sections. The PU foam shall have high resilience and radiolucent property.

All MS parts are passed through 8 tank Pretreated & powder coated process.

SS parts finished with Matt Polish.

All Process Parameters to be as per documented IMS Procedures for Quality Assurance ( ISO 9001:2008

Over all Size: 2155mm L when extended x 1010 mm W x 520 mm To 880 mm H (Without Mattress).

Three section high pressure laminated top. It shall have detachable laminated top for middle section and leg section for ease of cleaning.

Leg section can be telescoped under backrest for lithotomy position.

Backrest, trendelenburg & reverse trendelenburg and height adjustment position operated by Electro mechanical adjustment thru hand set; battery backup with inbuilt battery charger shall be provided. The hand set shall have indications for power on and the battery charge.

All electro mechanical actuators need to be compatible with class of IP 54.

The bed shall have work simultaneously on two actuators system for raising and lowering height. Bed frame made mainly from 60 x30mm x 1.6mm mm thick ERW tube with proper support. This frame shall be fitted on the base frame mainly made of 60 x 30 x 1.6mm ERW tubes on various supporting links.

The base frame shall be mounted on 125mm dia non-rusting castor wheels with central and directional locking mechanism and pedal operated at the head end of the bed. Castor made from high grade non floor-staining synthetic materials with integrated thread guards. Wheel centre having precision ball bearing to run smoothly.

The bed shall have easily detachable moulded head & foot side panels. Four corner rubber buffers.

Bed shall have swing down type railings; Railing shall be made from non-rusting moulded material. These shall be fitted to the mattress support sections and should be able to raise and lock through spring lock mechanism through an operating lever.

S.S. saline rod with 12mm dia S.S. rod shall telescope in SS socket tube approx 15.8 mm dia x 18G welded on angular base bracket of 14G SS sheet. Nylon bracket provided to prevent colour damage It could be placed at two different locations.

Patient's bearing down handgrips should be made of 22mm dia 18 G stainless steel tube fixed with PVC handle and should have location adjustability for patient's convenience.

A pair of upholstery aluminum lithotomic crutches mounted on S.S. rods.

Waste collecting removable stainless steel tray shall be provided at perennial recess.

It shall have foot support for high / low chair position.

The backrest and middle section shall have 75 mm thickness foam mattress P.U. 40 D. with rexine cover and zip. The leg section shall have 130mm thickness for propose alignment with other adjacent sections. The PU foam shall have high resilience and radiolucent property.

All MS parts are passed through 8 tank Pretreated & powder coated process.

SS parts finished with Matt Polish.

All Process Parameters to be as per documented IMS Procedures for Quality Assurance ( ISO 9001:2008

### **LED (PORABLE LIGHT):**

Luminance: ,25,000 Lux,  
Spot Diamter : 100-125  
Depth illumination : 10-15cm  
Colour Temp. : 3200-5200 K  
Colour Reduction Index 91Ra  
Focusing :Manual  
LED Average Life: > 50000 Hrs  
Number of LED: 76  
Diameter of Light 580mm  
Intensity Control 10-100 Digital  
Power Supply: 220V/50Hz

U.T. Administration of Daman and Diu  
Office of the Medical Superintendent  
Govt. Hospital, Daman

SPECIFICATION FOR SURGICAL EQUIPMENT AND HOSPITAL FURNITURE

E-Tender Notice No. GHD/E-Tender/ 2014-2015/2667

dated:- 19 .01.2015

TENDER FORM FOR FINANCIAL BID

Sr.No.	Name of the Item	Unit	Rate/ Unit
	Rate quoted as per technical specifications		Rate must be submitted online only on <a href="http://www.nprocure.com">www.nprocure.com</a>
01	I.C.U. BED SHOULD ON FULLY MOTORISED WITH A PRESS OF A BUTTON CARDIAC CHAIR POSITION (With Accessores)	Per nos	
02	<u>Crash Cart</u>	Per nos	
03	<u>Multi Treatment Chair</u> (With Accessories)	Per nos	
04	EMERGENCY AND RECOVERY TROLLEY (With Accessories)	Per nos	
05	<u>Rigid (Fixed Wheel Chair)</u>	Per nos	
06	<u>Birthing Bed (Motorised)</u>	Per nos	
07	<u>LED (PORABLE LIGHT):</u>	Per nos	

8