



प्रदूषण नियंत्रण समिति  
Pollution Control Committee

000020  
2A

दमण एवं दीव तथा दा.न.ह.  
Daman & Diu and Dadra Nagar Haveli  
फोर्ट एरिया, मोटी दमण / Fort Area, Moti Daman, दमण / Daman.

CATEGORY - II (OPERATE)

Consent No. PCC/DDD/O-2656/WA/AA/AM/15-16/87

Date :- 13/05/16

In exercise of the powers delegated to the Pollution Control Committee, Daman, Diu and Dadra & Nagar Haveli by the Central Pollution Control Board vide notification No.B-12015/7/92 published in the gazette of India No.746 dated 26/11/1992 and administration order No.45/1(1)/92-F&E/4700 dated 8/2/1993, the consent is hereby granted under Section 25, Sub section (1) & (2) of Water (Prevention & Control of Pollution) Amended Act, 1988 and under Section 21 of Air (Prevention & Control of Pollution) Act, 1981 and the rules and orders made there under to manufacture below mentioned products at the below mentioned address subjected to the following terms and conditions.

Consent is granted to:

**M/s. Trexol Lube Industries,**  
**Sr. no. 909/1, Shed no.3A,**  
**Opp. Electronic Industrial Estate,**  
**66 KVA Road, Village Amli,**  
**Silvassa.**

1. The Consent to **Operate** is granted for a period upto **30/04/2017**.
2. The Consent is valid for the manufacture of following items:

Sr. No.	Product	Maximum Production Quantity
1.	Lubricating oil/Speciality Oil/Conning Oil	450 MTPA
2.	Grease	50 TPA
3.	Petroleum Jelly	50 TPA

3. Conditions under Water Act:

- 3.1 The daily quantity of trade effluent from the factory shall be NIL.
- 3.2 The daily quantity of sewage from the factory shall not exceed 10 Lit/Day.
- 3.3 Trade Effluent: If any the quality of the treated effluent as per PCC norms mentioned below.

(1)	pH	Between	6.5-9.0
(2)	Suspended Solids	Not to exceed	100 mg/L.
(3)	BOD, 3 days, 27°C	Not to exceed	100 mg/L.
(4)	C.O.D.	Not to exceed	250 mg/L.
(5)	Oil & Grease	Not to exceed	10 mg/L.

3.4 Trade Effluent Disposal Outlet Conditions: Industry shall not discharge treated effluent outside factory premises. The treated effluent shall be reused/recycled/Incinerated or used for plantation /gardening within the factory premises:

3.5 Sewage Treatment - Domestic effluent shall be disposed off through septic tank/soak pit system to conform to the following standards.

BOD (5 days at 20 <sup>o</sup> C)	less than 20 mg/l
Suspended solids	less than 30 mg/l
Residual Chlorine	minimum 0.5 mg/l

- 3.6 The unit shall not carry out any kind of washing process in manufacturing process.
- 3.7 The unit shall not generate any kind of hazardous waste from the manufacturing process.

